



COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

ALVI Officine Meccaniche E. Viazzo & C. s.r.l.
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA
Tel. +39 0161 234600 - Fax +39 0161 234633
E-mail: hil@alvi-italia.com - www.alvi-italia.com
Cod. fisc./P.I. 00162290027 - R.E.A. VC-104795 - Cap. Soc. € 1.500.000

Art. BA20 1-2-1



| | |
|----------------------|------------------------------|
| Codice | RABA20ON002 |
| Name | BA 20 |
| Internal dim. | 1000 x 500 x 610 mm H |
| External dim. | 1030 x 530 x 770 mm h |
| Wheels diam. | 100 mm |
| Disp. | 1-2-1 |
| Weight | 16.70 kg |
| Litres | 305 Lt |

Body in light alloy sheet, anodised (10 micron) with ribbed walls. Not perforated. Upper rim dia. 20 mm. with inner strengthening. Bottom frame and buffer profiles in light alloy. 2 fixed and 2 swivelling wheels with non marking grey rubber ring, zinc plated brackets, position 1-2-1.



COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

ALVI Officine Meccaniche E. Viazzo & C. s.r.l.
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA
Tel. +39 0161 234600 - Fax +39 0161 234633
E-mail: hil@alvi-italia.com - www.alvi-italia.com
Cod. fisc./P.I. 00162290027 - R.E.A. VC-104795 - Cap. Soc. € 1.500.000

Art. BA20 1-2-1



| | |
|----------------------|------------------------------|
| Codice | RABA20ON004 |
| Name | BA 20 |
| Internal dim. | 1000 x 600 x 610 mm H |
| External dim. | 1030 x 630 x 770 mm h |
| Wheels diam. | 100 mm |
| Disp. | 1-2-1 |
| Weight | 17.80 kg |
| Litres | 366 Lt |

Body in light alloy sheet, anodised (10 micron) with ribbed walls. Not perforated. Upper rim dia. 20 mm. with inner strengthening. Bottom frame and buffer profiles in light alloy. 2 fixed and 2 swivelling wheels with non marking grey rubber ring, zinc plated brackets, position 1-2-1.



COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

ALVI Officine Meccaniche E. Viazzo & C. s.r.l.
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA
Tel. +39 0161 234600 - Fax +39 0161 234633
E-mail: hil@alvi-italia.com - www.alvi-italia.com
Cod. fisc./P.I. 00162290027 - R.E.A. VC-104795 - Cap. Soc. € 1.500.000

Art. BA20 1-2-1



| | |
|----------------------|-----------------------------|
| Codice | RABA20ON010 |
| Name | BA 20 |
| Internal dim. | 920 x 680 x 685 mm H |
| External dim. | 950 x 710 x 875 mm h |
| Wheels diam. | 125 mm |
| Disp. | 1-2-1 |
| Weight | 20.40 kg |
| Litres | 428 Lt |

Body in light alloy sheet, anodised (10 micron) with ribbed walls. Not perforated. Upper rim dia. 20 mm. with inner strengthening. Bottom frame and buffer profiles in light alloy. 2 fixed and 2 swivelling wheels with non marking grey rubber ring, zinc plated brackets, position 1-2-1.



COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

ALVI Officine Meccaniche E. Viazzo & C. s.r.l.
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA
Tel. +39 0161 234600 - Fax +39 0161 234633
E-mail: hil@alvi-italia.com - www.alvi-italia.com
Cod. fisc./P.I. 00162290027 - R.E.A. VC-104795 - Cap. Soc. € 1.500.000

Art. BA20 1-2-1



| | |
|----------------------|------------------------------|
| Codice | RABA20ON006 |
| Name | BA 20 |
| Internal dim. | 1300 x 700 x 610 mm H |
| External dim. | 1330 x 730 x 805 mm h |
| Wheels diam. | 125 mm |
| Disp. | 1-2-1 |
| Weight | 25.00 kg |
| Litres | 555 Lt |

Body in light alloy sheet, anodised (10 micron) with ribbed walls. Not perforated. Upper rim dia. 20 mm. with inner strengthening. Bottom frame and buffer profiles in light alloy. 2 fixed and 2 swivelling wheels with non marking grey rubber ring, zinc plated brackets, position 1-2-1.



COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

ALVI Officine Meccaniche E. Viazzo & C. s.r.l.
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA
Tel. +39 0161 234600 - Fax +39 0161 234633
E-mail: hil@alvi-italia.com - www.alvi-italia.com
Cod. fisc./P.I. 00162290027 - R.E.A. VC-104795 - Cap. Soc. € 1.500.000

Art. BA20 1-2-1



| | |
|----------------------|------------------------------|
| Codice | RABA20ON008 |
| Name | BA 20 |
| Internal dim. | 1300 x 700 x 685 mm H |
| External dim. | 1330 x 730 x 880 mm h |
| Wheels diam. | 125 mm |
| Disp. | 1-2-1 |
| Weight | 27.00 kg |
| Litres | 623 Lt |

Body in light alloy sheet, anodised (10 micron) with ribbed walls. Not perforated. Upper rim dia. 20 mm. with inner strengthening. Bottom frame and buffer profiles in light alloy. 2 fixed and 2 swivelling wheels with non marking grey rubber ring, zinc plated brackets, position 1-2-1.